

**TILTING TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.**



|                                                                      |                     |
|----------------------------------------------------------------------|---------------------|
| <b>Max drilling capacity on cast iron with pre-drilling hole</b>     | Ø 32 mm             |
| <b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b> | Ø 28 mm             |
| <b>Continuous drilling capacity</b>                                  | Ø 20 mm             |
| <b>Spindle taper</b>                                                 | CM 4                |
| <b>Chuck sizes</b>                                                   | 5 - 20 mm B22       |
| <b>Spindle speed</b>                                                 | (12) 150 - 2450 rpm |
| <b>Spindle travel</b>                                                | 120 mm              |
| <b>Quill</b>                                                         | Ø 62 mm             |
| <b>Column</b>                                                        | Ø 92 mm             |
| <b>Height</b>                                                        | 1710 mm             |
| <b>Distance column-chuck</b>                                         | 260 mm              |
| <b>Table dimensions</b>                                              | 460 x 425 mm        |
| <b>Slot</b>                                                          | 14 mm               |
| <b>Tilting table</b>                                                 | ± 45°               |
| <b>Motor</b>                                                         | 230 V 50 Hz 1,5 kW  |
| <b>Net weight</b>                                                    | 126 kg              |
| <b>Packaging dimensions</b>                                          | 1430x660x330 h mm   |
| <b>Gross weight</b>                                                  | 132,00 kg           |
| <b>EAN Code</b>                                                      | 8012667197551       |

**Included**

Keyless chuck 5 - 20 mm B22  
Drill chuck shank MT 4